

QUICK REFERENCE GUIDE



FRONTMOUNT™ MODELS		500V Series Air-Cooled		600 Series Air-Cooled		700 Series Air-Cooled						700 Series Liquid-Cooled			900 Series Air-Cooled			900 Series Liquid-Cooled						
Model #/Fuel Type	525V-42 Gas	526V-52 Gas	623T Gas	725KT Gas	727T EFI Gas	735BT Gas	725DT Diesel	729T Gas	940 EFI Gas	900 1.L Diesel	932 Gas	50V Series	60 Series	70/90 Series	50V Series	60 Series	70/90 Series	50V Series	60 Series	70/90 Series				
Limited Warranty Highlights	Commercial: 2 yr. 800 hours/Residential: 4 yr. 800 hours						Commercial: 3 yr. Unlimited hours/Residential: 4 yr. 800 hours						1.31, 1.26, 1.25 Kubota MaxTorque™ 3-cyl.											
Engine	724cc B&S CXi V-twin	810 cc Vanguard V-twin	694 cc Rehko Command Pro V-twin	747 cc Rehko Command Pro V-twin	747 cc Rehko Command Pro EFI V-twin	993 cc Vanguard Big Block V-twin	898 cc Kubota MaxTorque™ 3-cyl.	962 cc Kubota MaxTorque™ 3-cyl.	993 cc Vanguard Big Block V-twin	1.31, 1.26, 1.25 Kubota MaxTorque™ 3-cyl.	992 cc Kubota MaxTorque™ 3-cyl.	Horizontal: Uniform cooling, air flow and internal lubrication						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.						
Crankshaft	Vertical						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.					
Air Filter	Integrated, cyclonic air cleaner with 5-step debris management system.	Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management.	Heavy-duty, cyclonic, remote-mounted, replaceable dual element.						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.						Heavy-duty, cyclonic, remote-mounted, replaceable dual element.									
Fuel Capacity	4.0 gal.	4.0 gal.	7.2 gal.	8.0 gal.	7.2 gal.	14.4 gal. (two 7.2-gal. tanks)	8.0 gal.	7.2 gal.	Horizontal: Uniform cooling, air flow and internal lubrication						Horizontal: Uniform cooling, air flow and internal lubrication									
LED Lights	Optional. Plug-in ready. Improves visibility while mowing.						Standard: Greater visibility while mowing.						Standard: Greater visibility while mowing.						Standard: Greater visibility while mowing.					
Hydraulic Drive System with cooling fans	Design-matched, fully hydraulic Parker HTE Series with variable displacement piston-type pumps, and high-torque wheel motors for each drive wheel with in-line cooling fans.	Design-matched T-Drive™ hydrostatic drive systems with tandem 12 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.	Design-matched T-Drive™ hydrostatic drive systems with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.	Design-matched T-Drive™ hydrostatic drive systems with tandem 21 cc piston-type pump, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.	Design-matched T-Drive™ hydrostatic drive systems with tandem 21 cc piston-type pump, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.	Horizontal: Uniform cooling, air flow and internal lubrication						Horizontal: Uniform cooling, air flow and internal lubrication						Horizontal: Uniform cooling, air flow and internal lubrication						
Max Ground Speed	0 - 8.0 mph	0 - 8.5 mph	0 - 9.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	0 - 10.0 mph	Horizontal: Uniform cooling, air flow and internal lubrication						Horizontal: Uniform cooling, air flow and internal lubrication						
Seat	Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability.						Premier suspension seat, adjustable for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slide forward and aft. Covered with CoolTemp Cordura® fabric.						Premier suspension seat, adjustable for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slide forward and aft. Covered with CoolTemp Cordura® fabric.						Premier suspension seat, adjustable for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slide forward and aft. Covered with CoolTemp Cordura® fabric.					
Suspension	Iso-Mounted seat/footrest.	Anti-Vibe Power Platform®						Iso-Mounted seat/footrest.						Iso-Mounted seat/footrest.						Iso-Mounted seat/footrest.				
Steering Levers	ComfortReach™ adjustable dual steering levers. Dampened, return to neutral from forward or reverse. (Optional QuikAjust Tilt™ levers)	QuikAjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.						QuikAjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.						QuikAjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.						QuikAjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.				
Cutting Width	42"	52"	48"	52"	52"	61"	52"	61"	72"	61"	72"	52"	61"	72"	61"	72"	61"	72"	61"	72"	61"	72"		
PowerFold® Electric Deck Lift	All FrontMount™ decks feature the exclusive PowerFold® feature. Rotate the cutting deck to a near vertical position for easy cleaning and servicing of the underside of the deck. Also electrically changes cutting height at the touch of a switch. Provides a shorter footprint of the FrontMount™ tractor/deck unit in order to fit more on a trailer and for compact storage.						The same combo deck easily converts from side discharge to optional DownDischarge™ mulching or PowerVac™ Collection.						The same combo deck easily converts from side discharge to optional DownDischarge™ mulching or PowerVac™ Collection.						The same combo deck easily converts from side discharge to optional DownDischarge™ mulching or PowerVac™ Collection.					
Combo Deck Model #	3242	3252	3348	3452	3452	3661	3452	3661	3472	3661	3472	3452	3661	3472	3661	3472	3661	3472	3661	3472	3661	3472		
Dedicated Rear Discharge Decks Model #	NA	NA	NA	3552*	3552	3761	3552	3761	3572	3761	3572	3552	3761	3572	3761	3572	3761	3572	3761	3572	3761	3572		
Cutting Height Range	2.0 - 4.5 inches	1.25 - 5.0 inches						1.25 - 5.0 inches						1.25 - 5.0 inches						1.25 - 5.0 inches				
Deck Construction	Extra-deep 5.5" deck (4.5" on 3348) with anvil-edge front design improves grass lift. Robotically welded, high-strength U.S. steel deck with double-layered, formed spindle plane is nearly 1-inch thick in stress zones. Half-inch reinforcement on leading edge of deck. Massive 8-inch Sentry™ spindle flanges, anchored in a 6-bolt pattern, spread the force of impact for greater strength and cut.						Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Quik-D-Tatch® feature allows deck to be removed to add implements. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection. 61- and 72-inch decks feature a spindle shaft drive.						Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Quik-D-Tatch® feature allows deck to be removed to add implements. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection. 61- and 72-inch decks feature a spindle shaft drive.						Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Quik-D-Tatch® feature allows deck to be removed to add implements. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection. 61- and 72-inch decks feature a spindle shaft drive.					
Hydraulic Lift	NA						Optional - Lifts deck to clear curbs and trailer ramps						Standard - Lifts deck to clear curbs and trailer ramps						Standard - Lifts deck to clear curbs and trailer ramps					
Deck Wheels	9 x 3.5-4 flat-proof						11 x 4-5 flat-proof	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic		
Drive Tires Turf and bar tread tire options available	20 x 8-10 Turf	20 x 10-8 Turf*	22 x 11-10 Bar Tread						22 x 11-10 Bar Tread						22 x 11-10 Bar Tread						22 x 11-10 Bar Tread			
Tail Wheels 13 x 6.5-6	Single-Fork	Wide-Stance, Single-Fork	Single-Fork	Wide-Stance, Single-Fork						Wide-Stance, Single-Fork						Wide-Stance, Single-Fork						Wide-Stance, Single-Fork		

*623T, equipped with 3552 (rear discharge) deck requires 22 x 11-10 turf, 22 x 11-8 bar tread or 22 x 11-12 Tread® drive tires.

See your dealer for specifications on specific models or visit grasshoppermower.com.

© 2015 The Grasshopper Company. Form 295-10703 Litho in U.S. Made only by Grasshopper®.

MidMount™ Accessory and Implement Chart							
	100V Series	200V-G4 Series	200 M1 Series	300 M1 Series	400 M1 Series	300G Series	Stand-O Series
Edge-EZE™	●	●	●	●	●	●	●
PowerVac™ 8F/8HT	●	●	●	●	●	●	●
PowerVac™ 12F/12HT			●	●	●	●	●
PowerVac™ Model 16			●	●	●		
Electric Height Adjustment			●	AC Models			
Hydraulic Height Adjustment				LC Models 61" and larger decks	Std.	61" and larger decks	
4X Rear Discharge Decks	48-in. and larger decks	●	●	●	●		
DuraFlex Suspension Forks	48-in. and larger decks	●	●	●	●	●	●
53" Shielded Sprayer			●	●	●	●	
Side Discharge Control Kit	48-in. and larger decks	●	●	●	●	●	●
Sunshade Canopy	Aluminum or Vinyl						
Premier Suspension Seat			●	●	●	328G4 Only	
Footrest Riser							●
Michelin® X® Tweel® 24 x 12-12 Drive Tires		●	●	●	●	●	
Michelin® X® Tweel® 13 x 6.5-6 Front Tires		●	●	●	●	●	