

200 SERIES AIR-COOLED MIDMOUNT™

Reliable economy in a compact package



ComfortReach™ with "no tools" 2-in. adjustment range



225

48 52 61

747 cc, 2-cylinder Kohler Command Pro OHV horizontal crankshaft gasoline engine

● Standard deck ■ DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61")
- » TrimAide™ Roller (52")
- » Electric height adjustment
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » Taller steering levers
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Adjustable cup holder

Reliable economy that delivers a quality cut and powerful, air-cooled performance in a compact package ideal for tight-quarters mowing. Enjoy the maneuverability of a walk-behind without the fatigue, to mow longer and deliver quality results.

DURABILITY & LONGEVITY

The horizontal crankshaft configuration adds performance life to the engine. A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

Design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

MANICURED CUT

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® and coil-spring suspension provides all-day comfort. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 9.5 MPH and 5.27 acres/hr. based on 61" cutting width*
For more details visit: grasshoppermower.com/acres



- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (61")
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Aluminum or Vinyl Sunshade Canopy
- » Yellow beacon light
- » Side discharge control kit
- » Air Dam kit - for dry, dusty conditions
- » String trimmer mount kit

AIR-COOLED 200 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	Standard Option	225 48"	225 52"	225 61"	MODEL - CUTTING WIDTH	Standard Option	225 48"	225 52"	225 61"
ENGINE									
Type/Displacement/Cylinders									
Kohler Command Pro / 45.6 cu. in. (747cc) / V-Twin		●	●	●	TRANSMISSION & STEERING				
Crankshaft/Cooling System									
Horizontal / Air		●	●	●	Type				
Fuel/Capacity									
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)		●	●	●	Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 12cc piston-type pumps and high-torque Parker wheel motors.		●	●	●
Air Cleaner						Filtration/Hydro Fluid			
Heavy-duty, remote-mounted engine air cleaner with replaceable element		●	●	●	7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max [®] fluid withstands high and low temperature extremes for 1,000-hour change intervals.		●	●	●
DECKS - Side Discharge or Dedicated 4X Rear Discharge (4XRD)						Speed			
Construction (Robotic-welded steel) - Side discharge or optional 4X Rear Discharge									
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.		●	●	●	0 - 8.5 mph (0 - 13.7 kph) forward		●		
DuraMax [®] deck			●	●	0 - 9.0 mph (0 - 14.5 kph) forward			●	
Blades (MARBAIN[®], 1/4-in.)									
(2) 18 in. (45.7 cm), (1) 15 in. (38.1 cm) - high-lift blades standard		●			0 - 9.5 mph (0 - 15.3 kph) forward			●	
(3) 18 in. (45.7 cm) - high-lift blades standard			●		0 - 6.0 mph (0 - 9.7 kph) reverse		●	●	●
(3) 21 in. (53.3 cm) - high-lift blades standard				●					
Sentry[™] Spindle Assemblies									
Sentry [™] Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.		●	●	●	Turning Radius				
Spindle Housing - 8-in. (20.3 cm)-diameter with 6-bolt pattern									
Machined aluminum		●	●	●	True zero degree, turns within own length with counter-rotating, independently powered drive wheels.		●	●	●
QuikAjust[™] DropPin[™] Height Adjustment						Steering			
Foot-controlled height adjustment pedal with pin		●	●	●	One- or two-handed operation with ComfortReach [™] adjustable Hydra-Smooth [™] dual levers that automatically return to neutral from either forward or reverse position.		●	●	●
Cutting Height Range						Brakes			
1.0 - 5.0 in. (2.5 - 12.7 cm)		●	●	●	Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.		●	●	●
Blade Drive						Disc brakes			
Belt drive with single Kevlar [®] V-belt and idler arm tensioning		●	●	●			●	●	●
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information						Clutch			
4th Spindle and Grass Thrower Blade						Heavy-duty electric MagStop blade clutch/brake			
Cast iron thrower spindle housing - 5-in. (12.7 cm)-diameter with 4-bolt pattern		●	●	●		●	●	●	●
(1) Grass Thrower Blade		●	●		POWER UNIT TIRE SIZES				
(1) 18 in. High-Low Mulching Grass Thrower Blade				●	Drive Wheels (4-ply rated): 23 x 9.5-12 turf		●		
STARTER & ELECTRICAL SYSTEM						Drive Wheels (4-ply rated): 23 x 10.5-12 turf		●	
Maintenance-Free Battery/Charging Capacity/Starter						Drive Wheels (4-ply rated): 24 x 12-12 turf			●
12 volt/15 amp/solenoid shift		●	●	●	Drive Wheels (4-ply rated): 24 x 12-12 bar tread			○	
Ignition						Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap		●	●
Breakerless		●	●	●					
Interlock System									
Prevents engine start when PTO clutch is engaged or steering levers are in drive position.		●	●	●	POWER UNIT DIMENSIONS WITH DURAMAX[®] DECKS				
Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.		●	●	●	Mulch or 4XRD Width*/Length: 49.5 in. (125.7 cm) / 76.5 in. (194.3 cm)		●		
ULTIMATE OPERATOR STATION[™]						Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 76.5 in. (194.3 cm)		●	
Premium Comfort Seat						Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 78.0 in. (198.1 cm)		●	
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura [®] -covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.		●	●	●					
Premier Suspension Seat		○	○	○	*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised.				
Operator Protection						*Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.			
ROPS with seat belt		●	●	●	Height (seat back/seat cushion): 46.5 in. (118.1 cm) / 31.0 in. (78.7 cm)		●	●	
Suspension						Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)			●
InFrame [™] suspension with iso-mounted seat and footrest		●	●	●	Height (ROPS): 70.0 in. (177.8 cm)	●	●	●	
Console-Mounted Instruments									
Low engine oil pressure light, combination electronic fuel gauge/hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.		●	●	●	WEIGHT				
Work Lights (Pre-wired)						Uncrated ^{**} : 1050 lbs. (476.3 kg)		●	
LED		○	○	○	Uncrated ^{**} : 1070 lbs. (485.4 kg)		●		
** Mulching package kit weights with high-low mulching blades:									
48-in. - 25 lbs. (11.3 kg); 52-in. - 29 lbs. (13.2 kg); 61-in. - 36 lbs. (16.3 kg).									



Featured Model 225 with 52-inch DuraMax[®] deck