

300 SERIES LIQUID-COOLED MIDMOUNT™

Torque and power available on demand



ComfortReach™ with "no tools" 2-in. adjustment range

329

52 61 72

962 cc, 3-cylinder,
MaxTorque™
horizontal crankshaft
gasoline engine

325D

52 61 72

898 cc, 3-cylinder,
MaxTorque™
Clean Diesel horizontal
crankshaft engine

► DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61" and 72")
- » TrimAide™ Roller (52")
- » Electric height adjustment
- » Hydraulic height adjustment (61" and 72")
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Aluminum or Vinyl Sunshade Canopy
- » Yellow beacon light
- » Filter minder
- » Radiator cleaning wand
- » Engine block heater
- » Side discharge control kit
- » Air Dam kit - for dry, dusty conditions
- » String trimmer mount kit

Long-lasting performance with a higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

Designed for fuel economy and extended service life for operating efficiency. Equipped with a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine, so you can tackle even the toughest jobs with the greatest of ease. The engine is mounted with horizontal crankshaft for longer performance life.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

MANICURED CUT

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal / 45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 10.5 MPH
and 6.88 acres/hr. based on
72" cutting width.*
For more details visit:
grasshoppermower.com/acres



LIQUID-COOLED 300 SERIES-SPECIFICATIONS


MODEL - CUTTING WIDTH	● Standard ○ Option	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"	
ENGINE														
Type/Displacement/Cylinders														
Kubota MaxTorque™ / 54.8 cu. in. (898 cc) / 3-cyl.														
Kubota MaxTorque™ / 58.7 cu. in. (962 cc) / 3-cyl.														
Crankshaft/Cooling System														
Horizontal / Liquid														
Fuel/Capacity														
Diesel - No. 2 / 12 U.S. Gal. (45.4 l)														
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)														
Air Cleaner														
Heavy-duty, remote-mounted engine air cleaner with replaceable element														
DECKS - Side Discharge or Dedicated 4X Rear Discharge (4XRD)														
Construction (Robotic-welded steel) - Side discharge or optional 4X Rear Discharge														
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.														
DuraMax® deck														
Blades (MARBAIN®, 1/4-in.)														
(3) 18 in. (45.7 cm) - high-lift blades standard														
(3) 21 in. (53.3 cm) - high-lift blades standard														
(3) 25 in. (63.5 cm) - high-lift blades standard														
Sentry™ Spindle Assemblies														
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.														
Spindle Housing - 8-in. (20.3 cm)-diameter with 6-bolt pattern														
Machined aluminum														
QuikAjust™ DropPin™ Height Adjustment														
Foot-controlled height adjustment pedal with pin														
Cutting Height Range														
1.0 - 5.0 in. (2.5 - 12.7 cm)														
Blade Drive														
Belt drive with single Kevlar® V-belt and idler arm tensioning														
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information														
4th Spindle and Grass Thrower Blade														
Cast iron thrower spindle housing - 5-in. (12.7 cm) -diameter with 4-bolt pattern														
(1) Grass Thrower Blade														
(1) 18 in. High-Low Mulching Grass Thrower Blade														
STARTER & ELECTRICAL SYSTEM														
Maintenance-Free Battery/Charging Capacity/Starter														
12 volt/40 amp/solenoid shift														
Ignition														
Breakerless														
Diesel quick heat glow plug														
Interlock System														
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.														
ULTIMATE OPERATOR STATION™														
Premium Comfort Seat														
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.														
Premier Suspension Seat														
Operator Protection														
ROPS with seat belt														
Suspension														
InFrame™ suspension with iso-mounted seat and footrest														
For a complete list of trademarks/registered trademarks, visit grasshoppermower.com/legal . Litho in U.S.A. Form 102324 © 2024 The Grasshopper Company														
MODEL - CUTTING WIDTH														
Console-Mounted Instruments														
Low engine oil pressure, combination electronic fuel gauge/hour meter, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, ignition and push/pull PTO switches.														
Choke integrated with throttle lever														
Glow plug														
Work Lights (Pre-wired)														
LED														
TRANSMISSION & STEERING														
Type														
Design-matched G2 hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.														
Filtration/Hydro Fluid														
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.														
Speed														
0 - 10 mph (0 - 16.1 kph) forward														
0 - 10.5 mph (0 - 16.9 kph) forward														
0 - 6.0 mph (0 - 9.7 kph) reverse														
Turning Radius														
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.														
Steering														
One- or two-handed operation with ComfortReach™ adjustable Hydro-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.														
Brakes														
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.														

300 SERIES AIR-COOLED MIDMOUNT™

Unexpected power in the straightaways



ComfortReach™ with "no tools" 2-in. adjustment range



DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61" and 72")
- » TrimAide™ Roller (52")
- » Electric height adjustment
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Aluminum or Vinyl Sunshade Canopy
- » Yellow beacon light
- » Filter minder
- » Side discharge control kit
- » Air Dam kit - for dry, dusty conditions
- » String trimmer mount kit

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

Power, efficiency and economy-equipped with a heavy-duty, Vanguard Big Block engine, with horizontal crankshaft for longer performance life, giving you intense mowing power in a surprisingly compact design.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

MANICURED CUT

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

COMFORT & ERGONOMICS

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 10.5 MPH and 6.88 acres/hr. based on 72" cutting width*
For more details visit: grasshoppermower.com/acs



AIR-COOLED 300 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	● Standard ○ Option	335B 52"	335B 61"	335B 72"
ENGINE				
Type/Displacement/Cylinders				
B&S Vanguard Big Block / 60.6 cu. in. (993 cc) / V-twin	●	●	●	
Crankshaft / Cooling System				
Horizontal / Air	●	●	●	
Fuel / Capacity				
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	●	●	●	
Air Cleaner				
Heavy-duty, remote-mounted engine air cleaner with replaceable element	●	●	●	
DECKS - Side Discharge or Dedicated 4X Rear Discharge (4XRD)				
Construction (Robotic-welded steel) - Side discharge or optional 4X Rear Discharge				
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	●	●	●	
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm) - high-lift blades standard	●			
(3) 21 in. (53.3 cm) - high-lift blades standard		●		
(3) 25 in. (63.5 cm) - high-lift blades standard			●	
Sentry™ Spindle Assemblies				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	●	●	●	
Spindle Housing - 8-in. (20.3 cm)-diameter with 6-bolt pattern				
Machined aluminum	●	●	●	
QuikAjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin	●	●	●	
Cutting Height Range				
1.0 - 5.0 in. (2.5 - 12.7 cm)	●	●	●	
Blade Drive				
Belt drive with single Kevlar® V-belt and idler arm tensioning	●	●	●	
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information				
4th Spindle and Grass Thrower Blade				
Cast iron thrower spindle housing - 5-in. (12.7 cm) -diameter with 4-bolt pattern	●	●	●	
(1) 18 in. Grass Thrower Blade	●			
(1) 18 in. High-Low Mulching Grass Thrower Blade		●	●	
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 volt/20 amp/solenoid shift	●	●	●	
Ignition				
Breakerless	●	●	●	
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	●	
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	●	
Premier Suspension Seat	○	○	○	
Operator Protection				
ROPS with seat belt	●	●	●	

MODEL - CUTTING WIDTH	● Standard ○ Option	335B 52"	335B 61"	335B 72"
Suspension				
InFrame™ suspension with iso-mounted seat and footrest	●	●	●	
Console-Mounted Instruments				
Low engine oil pressure and parking brake warning lights, combination electronic fuel gauge/hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.		●	●	●
Work Lights (Pre-wired)				
LED		○	○	○
TRANSMISSION & STEERING				
Type				
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.		●	●	●
Filtration/Hydro Fluid				
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.		●	●	●
Speed				
0 - 10.0 mph (0 - 16.1 kph) forward		●		
0 - 10.5 mph (0 - 16.9 kph) forward			●	●
0 - 6.0 mph (0 - 9.7 kph) reverse		●	●	●
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.		●	●	●
Steering				
One- or two-handed operation with ComfortReach™ adjustable Hydro-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.		●	●	●
Brakes				
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.		●	●	●
Disc brakes		●	●	●
Clutch				
Heavy-duty electric MagStop blade clutch/brake		●	●	●
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 23 x 10.5-12 turf		●		
Drive Wheels (4-ply rated): 24 x 12-12 turf		○	●	●
Drive Wheels (4-ply rated): 24 x 12-12 bar tread		○	○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap		●	●	●
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS				
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 79.5 in. (201.9 cm)		●		
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 81.0 in. (205.7 cm)			●	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 84.5 in. (214.6 cm)				●
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.				
Height (seat back/seat cushion) 49.5 in. (125.7 cm) / 31.5 in. (80.0 cm)				
Height (seat back/seat cushion) 50.0 in. (127.0 cm) / 32.0 in. (81.3 cm)				
Height (ROPS): 70.0 in. (177.8 cm)				
WEIGHT				
Uncrated**: 1140 lbs. (517.1 kg)		●		
Uncrated**: 1190 lbs. (539.8 kg)			●	
Uncrated**: 1280 lbs. (580.6 kg)				●
**Mulching package kit weights with high-low mulching blades: 52-in. - 29 lbs. (13.2 kg); 61-in. - 36 lbs. (16.3 kg); 72-in. - 44 lbs. (20.0 kg)				