



Committed to the Cut.®

FRONTMOUNT™ MODELS	500V Series Air-Cooled		600 Series Air-Cooled		700 Series Air-Cooled								700 Series Liquid-Cooled				900 Series Air-Cooled		900 Series Liquid-Cooled							
Model #/Fuel Type	525V-42 Gas	526V-52 Gas	623T Gas		725KT Gas		727T EFI Gas		729BT Gas		735BT Gas		725DT Diesel		729T Gas		940 EFI Gas		900D 1.3L Diesel		932 Gas					
Limited Warranty Highlights	Commercial: 2 yr. 800 hours/Residential: 4 yr. 800 hours				Commercial: 3 yr. Unlimited hours/Residential: 4 yr. 800 hours																					
Engine	724cc B&S CXi V-twin	810 cc Vanguard V-twin	694 cc Kohler Command Pro V-twin		747 cc Kohler Command Pro V-twin		747 cc Kohler Command Pro EFI V-twin		896 cc Vanguard Big Block V-twin		993 cc Vanguard Big Block V-twin		898 cc Kubota MaxTorque™ 3-cyl.		962 cc Kubota MaxTorque™ 3-cyl.		993 cc Vanguard Big Block EFI V-twin with ETC		1.3L (1,262 cc) Kubota MaxTorque™ 3-cyl.		962 cc Kubota MaxTorque™ 3-cyl.					
Crankshaft	Vertical				Horizontal: Uniform cooling, air flow and internal lubrication																					
Air Filter	Integrated, cyclonic air cleaner with 5-step debris management system.	Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management.	Heavy-duty, cyclonic, remote-mounted, replaceable dual element.																							
Fuel Capacity	4.0 gal.		4.0 gal.		7.2 gal.								8.0 gal.		7.2 gal.		14.4 gal. (two 7.2-gal. tanks)		8.0 gal.		7.2 gal.					
LED Lights	Optional. Plug-in ready. Improves visibility while mowing.								Standard: Greater visibility while mowing.																	
Hydraulic Drive System with cooling fans	Design-matched, fully hydraulic Parker HTE Series with variable displacement piston-type pumps, and high-torque wheel motors for each drive wheel with in-line cooling fans.		Design-matched T-Drive™ hydrostatic drive systems with tandem 12 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.				Design-matched T6® hydrostatic drive systems with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. 1,000-hour fluid change intervals.								Design-matched G3 hydrostatic drive system with Hydro-Gear variable displacement 21 cc piston-type pumps, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.											
Max Ground Speed	0 - 8.0 mph		0 - 8.5 mph		0 - 9.0 mph		0 - 10.0 mph														0 - 11.0 mph					
Seat	Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability.																		Premier Suspension Seat adjusts for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slides fore and aft. Covered with CoolTemp™ Cordura® fabric.							
Suspension	Iso-Mounted seat/footrest.		Anti-Vibe Power Platform®														Iso-Mounted seat/footrest.									
Steering Levers	ComfortReach™ adjustable dual steering levers. Dampened, return to neutral from forward or reverse. (Optional QuikAdjust Tilt™ levers)				QuikAdjust Tilt™ Levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.																					
Cutting Width	42"	52"	48"	52"	52"	61"	52"	61"	72"	52"	61"	72"	61"	72"	52"	61"	72"	52"	61"	72"	61"	72"	61"	72"		
PowerFold® Electric Deck Lift	All FrontMount™ decks feature the exclusive PowerFold® feature. Rotate the cutting deck to a near vertical position for easy cleaning and servicing of the underside of the deck. Also electrically changes cutting height at the touch of a switch. Provides a shorter footprint of the FrontMount™ tractor/deck unit in order to fit more on a trailer, and for compact storage.																									
Combo Deck Model #	3242	3252	3348	3452	3452	3661	3452	3661	3472	3452	3661	3472	3661	3472	3452	3661	3472	3452	3661	3472	3661	3472	3661	3472		
Dedicated Rear Discharge Decks Model #	NA	NA	NA	3552*	3552	3761	3552	3761	3572	3552	3761	3572	3761	3572	3552	3761	3572	3552	3761	3572	3761	3572	3761	3572		
Cutting Height Range	2.0 - 4.5 inches				1.25 - 5.0 inches																					
Deck Construction	Extra-deep 5.5" deck (4.5" on 3348) with anvil-edge front design improves grass lift. Robotically welded, high-strength U.S. steel deck with double-layered, formed spindle plane is nearly 1-inch thick in stress zones. Half-inch reinforcement on leading edge of deck. Massive 8-inch Sentry™ spindle flanges, anchored in a 6-bolt pattern spread the force of impact for greater strength and level cut. Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Quik-D-Tatch® feature allows deck to be removed to add implements. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection. 61- and 72-inch decks feature a splined-shaft drive.																									
Hydraulic Lift	NA				Optional - Lifts deck to clear curbs and trailer ramps														Standard - Lifts deck to clear curbs and trailer ramps							
Deck Wheels	9 x 3.5-4 flat-proof				11 x 4-5 flat-proof	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	9 x 3.5-4 flat-proof	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic	11 x 4-5 flat-proof	13 x 6.5-6 pneumatic			
Drive Tires Turf and bar tread tire options available	20 x 8-10 Turf		20 x 10-8 Turf *		22 x 11-10 Bar Tread																		24 x 12-12 Bar Tread			
Tail Wheels 13 x 6.5-6	Single-Fork	Wide-Stance, Single-Fork	Single-Fork		Wide-Stance, Single-Fork																					

*623T, equipped with 3552 (rear discharge) deck requires 22 x 11-10 turf, 22 x 11-8 bar tread or 22 x 11-12 Tweel® drive tires.

See your dealer for specifications on specific models or visit grasshoppermower.com.

© 2024 The Grasshopper Company Form 0424-170930 Litho in U.S.A. Models may be shown with optional equipment.

FrontMount™ Accessory and Implement Chart			
	500V Series	600 Series	700/900 Series
AERA-vator™		40"	40"/60"
Dethatcher	526V-52/623T - 46"		46"/60"
Dozer Blades	48"		48"/60"
Edge-EZE™	526V-52	•	•
PowerVac™	8F/8HT	8F/8HT/12F/12HT	
PowerVac™ 15B		•	•
PowerVac™ HighLift™ 15B			•
PowerVac 25			•
Rear Discharge Decks		•*	•
Remote Vac		•	•
Side Discharge Control Kit	•	•	•
Shielded Sprayer		53"/133"	
Snowthrower	48"		48"/60"
Sunshade Canopy	Aluminum or Vinyl		
Turbine Blower			•
V-Plow			•
Winter Cab			•
Premier Suspension Seat		•	• (Std on 940)
Footrest Riser			•
Michelin® X® Tweel® 22 x 11-12 Drive Tires		•	700 Series
Michelin® X® Tweel® 24 x 12-12 Drive Tires			900 Series
Michelin® X® Tweel® 13 x 6.5-6 Deck Wheels (72")			•
Michelin® X® Tweel® 13 x 6.5-6 Tail Wheels	•	•	•

MIDMOUNT™ MODELS	100V Series Air-Cooled						200V-G4 Series Air-Cooled				200 Series Air-Cooled	300 Series Air-Cooled				300 Series Liquid-Cooled				400 Series Air-Cooled				400 Series Liquid-Cooled				300G Series EFI Air-Cooled						Stand-On Air-Cooled		MidMount™ Accessory and Implement Chart												
Model #/Fuel Type	125VB Gas		125V Gas		127V Gas		225V-G4 Gas		226V-G4 Gas		225 Gas		329B Gas		335B Gas		325D Diesel		329 Gas		440 EFI Gas				400D 1.3L Diesel				328G4 EFI Gas			337G5 EFI Gas			26 Series Gas			100V Series	200V-G4 Series	200 M1 Series	300 M1 Series	400 M1 Series	300G Series	Stand-On Series				
Limited Warranty Highlights	Commercial: 2 yr. 500 hours/Residential: 4 yr. 500 hours						Commercial: 2 yr. 800 hours/Residential: 4 yr. 800 hours						Commercial: 3 yr Unlimited hours/Residential: 4 yr 800 hours												Commercial: 3 yr Unlimited hr/Residential: 4 yr 800 hr								Commercial: 3 yr 1,000 hr/Residential: 4 yr 800 hr			Commercial: 3 yr 1,250 hr/Residential: 4 yr 800 hr			Commercial: 2 yr Unlimited hr									
Engine	724cc B&S CXi V-twin		747 cc Kohler Confidant V-twin		810 cc B&S CXi V-twin		747 cc Kohler Confidant V-twin		810 cc Vanguard V-twin		747 cc Kohler Command Pro V-twin		896 cc Vanguard Big Block V-twin		993 cc Vanguard Big Block V-twin		898 cc Kubota MaxTorque™ 3-cyl.		962 cc Kubota MaxTorque™ 3-cyl.		993 cc Vanguard Big Block EFI V-twin with ETC				1.3L (1,262 cc) Kubota MaxTorque™ 3-cyl				810 cc Vanguard EFI V-twin			993 cc Vanguard EFI V-twin			810 cc Vanguard V-Twin													
Crankshaft	Vertical						Horizontal: Uniform cooling, air flow and internal lubrication																		Vertical						Vertical																	
Air Filter	Integrated, cyclonic air cleaner with 5-step debris management system.		Heavy-duty, cyclonic with QuadClean™ multi-stage air filtration.		Integrated, cyclonic air cleaner with 5-step debris management system.		Heavy-duty, cyclonic with QuadClean™ multi-stage air filtration.		Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management.		Heavy-duty, remote-mount, replaceable dual element.												Heavy-duty, cyclonic, remote-mounted, replaceable dual element.				Heavy-duty, remote-mount, replaceable dual element, Filter Minder.				Heavy-duty, cyclonic remote-mounted dual cleaner with replaceable element.						Heavy-duty, cyclonic remote-mounted dual cleaner with replaceable element.											
Fuel Capacity	3 gal. – 41/6.5 gal. – 48		6.5 gal.				6.5 gal.						12 gal.												13 gal.						9.25 gal. total (twin tanks w/ fuel selector)																	
LED Lights	Optional. Plug-in ready. Improves visibility while mowing.																		Standard: Greater visibility while mowing.								Optional. Plug-in ready. Improves visibility while mowing.			Standard: Greater visibility while mowing.			Standard: Greater visibility while mowing.															
Hydraulic Drive System with cooling fans	Design-matched, fully hydraulic Parker HTE Series with variable displacement piston-type pumps, and high-torque wheel motors for each drive wheel with in-line cooling fans.						12 cc, heavy-duty G4 Hydro-Gear 4400 transmissions with integrated cooling fans and 1-3/8-inch axles deliver powerful, smooth response.						Design-matched G ² hydrostatic drive system with Hydro-Gear variable displacement piston-type pumps, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.						Design-matched G ² hydrostatic drive system with Hydro-Gear variable displacement 21 cc piston-type pumps, CoolFan™ pump cooling system, high-torque Parker wheel motors and 7-micron absolute filters. 1,000-hour fluid change intervals.				12 cc, heavy-duty G4 Hydro-Gear 4400 transmissions with integrated cooling fans and 1-3/8-in. axles deliver powerful, smooth response.			16 cc, heavy-duty G5 Hydro-Gear 5400 transmissions with integrated cooling fans and 1-3/8-in. axles deliver powerful, smooth response.			T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, and design-matched Parker high-torque wheel motors.																			
Max Ground Speed	0 – 7.5 mph – 41 0 – 8.0 mph – 48		0 – 8.0 mph				0 – 9.0 mph						0 – 8.5 mph – 48 0 – 9.0 mph – 52 0 – 9.5 mph – 61		0 – 10.0 mph – 52 0 – 10.5 mph – 61 & 72				0 – 10.0 mph – 52 0 – 10.5 mph – 61 & 72				0 – 11.0 mph								0 – 10.5 mph		0 – 11.0 mph		0 – 9.5 mph													
Seat	Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability. Seat on 124V-48 and all 125V and 127V models adjust fore and aft and have foldable armrests.						Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Foldable armrests are steel supported for extra durability. Adjusts fore and aft.						Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability.												Premier Suspension Seat for customized fit. Adjusts for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slides fore and aft. Covered with CoolTemp™ Cordura® fabric.								Deep-cushioned Premium Comfort Seat, iso-mounted with coil-spring suspension and padded lumbar support and armrests all covered with breathable, scuff-resistant CoolTemp Cordura® fabric. Armrests are steel supported for extra durability. Adjusts fore and aft.			Premier Suspension Seat for customized fit. Adjusts for operator weight, tilting backrest, adjustable lumbar support, foldable armrests, slides fore and aft. Covered with CoolTemp™ Cordura® fabric.			Extra-wide, extra-thick pad with embroidered Grasshopper logo. Command Center tower and pad features 4.5 inches of adjustable vertical range.									
Suspension	Iso-mounted footrest with Shock Impact Reduction System.												InFrame™ with iso-mounted seat/footrest.												InFrame™ with iso-mounted seat/footrest.												Iso-mounted seat/footrest with Shock Impact Reduction System.						Coil-spring suspension and dampeners					
Steering Levers	ComfortReach™ adjustable dual steering levers. Dampened, return to neutral from forward or reverse. (Optional QuikAjust Tilt™ levers on 48-inch and larger models)						QuikAjust Tilt™ levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.						ComfortReach™ RatchetEze™ 2-inch adjustment. Dampened, return to neutral from forward or reverse. (Optional QuikAjust Tilt™ levers)												QuikAjust Tilt™ levers with 9-inch adjustment. Dampened, return to neutral from forward or reverse.												Dampened, return to neutral when released from forward and reverse. Adjustable grip bar fits larger/smaller operators.											
Combo Deck Cutting Width	41"	48"	48"	52"	61"	52"	61"	52"	61"	48"	52"	61"	52"	61"	61"	72"	52"	61"	72"	52"	61"	72"	61"	72"	52"	61"	61"	72"	52"	61"	61"	72"	52"	61"	52"	61"												
4X Rear Discharge Cutting Width	NA	48"	48"	52"	61"	52"	61"	52"	61"	48"	52"	61"	52"	61"	61"	72"	52"	61"	72"	52"	61"	72"	61"	72"	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA													
Cutting Height Range	1.0 – 4.5 inches												1.0 – 5.0 inches												1.0 – 5.5 inches																							
Deck Construction	Extra-deep 5.5" deck (4.5" on 124V-41) with anvil-edge front design (except 124V-41) improves grass lift. Robotically welded, high-strength U.S. steel deck with double-layered, formed spindle plane is nearly 1-in. thick in stress zones. Half-inch reinforcement on leading edge of deck. Massive 8-inch Sentry™ spindle flanges, anchored in a 6-bolt pattern spread the force of impact for greater strength and level cut. Spindle guards eliminate material wrap. Quarter-inch-thick MARBAIN® blades hold their edge longer for a high-quality cut. Same deck easily converts from side discharge to optional DownDischarge™ mulching or collection.																																															
Drive Tires	20 x 10-8 Turf – 41 20 x 10-10 Turf – 48		20 x 10-10 Turf – 48 & 52 20 x 12-10 Turf – 61		20 x 10-10 Turf – 52 20 x 12-10 Turf – 61		23 x 10.5-12 Turf – 52 24 x 12-12 Turf – 61				23 x 9.5-12 Turf – 48 23 x 10.5-12 Turf – 52 24 x 12-12 Turf – 61		23 x 10.5-12 Turf – 52 24 x 12-12 Turf – 61		24 x 12-12 Turf				23 x 10.5-12 Turf – 52 24 x 12-12 Turf – 61 & 72				26 x 12-12 Turf				24 x 12-12 Turf			26 x 12-12 Turf			23 x 10.5-12 350 Mag															
Front Wheels	13 x 5-6 pneumatic	13 x 6.5- 6 rib tread – pneumatic						13 x 6.5- 6 rib tread – pneumatic																																								