

STAND-ON SERIES AIR-COOLED



Take your business
to the next level.

LIMITED WARRANTY†
2 YEAR
—UNLIMITED HRS—
COMMERCIAL



Stand-On 26-52

STAND-ON 26

52 61

810 cc, V-Twin, OHV
B&S Vanguard
gasoline engine

Command Center tower features 4.5" of infinitely variable height adjustment, raising and lowering the control levers and pad to accommodate taller and shorter operators.



► DuraMax® deck

OPTIONS

- » Down Discharge™ mulching packages
- » Speed-Trimming™ heavy-duty anti-scalp roller
- » Flat-proof front tires
- » Michelin® X® Tweel® Airless Front Tires (13 x 6.5-6)
- » DuraFlex™ suspension forks
- » Filter minder
- » Side discharge control kit
- » Air Dam Ki
- » Edge-EZE™ edger
- » String trimmer mount kit
- » Trash bucket kit

The Stand-On Series is designed for extreme operator proficiency and all-day ergonomic comfort. True ZeroTurn™ maneuverability, outstanding ease-of-use, effortless on/off and legendary Grasshopper cut quality combine to deliver superior performance.

DURABILITY & LONGEVITY

T-Drive™ hydrostatic drive system features tandem pumps-in-reservoir, internal filtration and inline CoolFan™ coupled with Parker high-torque wheel motors design-matched to the engine HP for increased efficiency and simplified maintenance.

Extra-deep, 5.5-inch DuraMax® decks, with anvil-edged design for exceptional durability, deliver superior airflow for better cut quality. Cutting height is effortlessly raised and lowered thanks to the smooth motion of the hand-operated lever.

Engine, T-Drive™ pump and deck smoothly move as one when raising and lowering the cutting height position to keep the drive belt on a uniform horizontal plane for extended life and zero power loss. The service-friendly design includes removable guards and easy access to grease points and filters.

Fleet managers will appreciate the commonality of parts between Stand-On models and the rest of the Grasshopper product line. Four tie-down points secure the mower on the trailer.

COMFORT & ERGONOMICS

The wide anti-slip platform is equipped with adjustable coil-spring suspension and dampeners, insulating the operator from vibrations, for a smooth, shock-reducing, floating-action ride and minimal bouncing.

The Command Center tower features an extra-wide, extra-thick pad with embroidered Grasshopper logo.

The Command Center tower provides 4.5 inches of adjustable range and is positioned to provide a panoramic view of the mowing environment. The intuitive tower design allows for easy reach of all switches, levers and controls. Integrated LED work lights and a deep phone/accessory tray with USB charging ports are standard.

TRACTION & CONTROL

Hydraulically dampened control levers that also provide responsive and effortless maneuvering—including one-hand operation—and return to neutral when released from forward and reverse. Adjustable grip bar accommodates larger and smaller reaches of different operators.

The compact wheelbase provides an incredible power-to-size ratio. Easily fit more units on trailers and maneuver through tighter spaces.

Every Grasshopper mower is designed with a low center of gravity for optimal traction and stability. The centralized location of the engine, T-Drive™ pump and dual fuel tanks on Stand-On models lowers the overall center of gravity, and a total fuel capacity of 9.25 gal/35.0 L reduces the need for frequent refueling.

Increase your productivity with speeds up to 9.5 mph and 5.27 acres per hour with a 61-inch cutting deck.*



STAND-ON SERIES-SPECIFICATIONS

| MODEL – CUTTING WIDTH | STAND-ON 52 | STAND-ON 61 |
|--|----------------|----------------|
| ENGINE | | |
| Type/Displacement/Cylinders | | |
| B&S Vanguard/49.4 cu. in. (810cc)/V-Twin | ● | ● |
| Lubrication System | | |
| Pressure Lube, Filter | | |
| Crankshaft / Cooling System | | |
| Vertical | | |
| Cooling System | | |
| Air | | |
| Fuel / Capacity | | |
| Gasoline - unleaded / 9.25 U.S. Gal. (35.0 l) total fuel capacity – twin tanks with fuel selector | | |
| Air Cleaner | | |
| Heavy-duty, cyclonic, remote-mounted engine dual cleaner with replaceable element | | |
| Muffler | | |
| Ultra-quiet, single, industrial type | | |
| DURAMAX® DECKS | | |
| Construction (Robotic-welded steel) | | |
| Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck. | | |
| Blades (MARBAIN®, 1/4-in.) | | |
| (3) 18 in. (45.7 cm) | ● | |
| (3) 21 in. (53.3 cm) | | ● |
| Spindle Assemblies | | |
| Sentry™ Spindle System, 2.5 cm (approx. 1 in.) outside diameter (O.D.) shaft; double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion. | | |
| Spindle Housing | | |
| 8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern | | |
| Spindle Cones | | |
| Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion | | |
| QuikAjust™ Height Adjustment | | |
| Hand-controlled height adjustment lever with lock/release button | | |
| Cutting Height Range | | |
| 1.0 – 5.5 in. (2.5 – 12.7 cm) in 1/4-inch increments | | |
| Blade Drive | | |
| Belt drive with single Kevlar V-belt & idler arm tensioning | | |
| STARTER & ELECTRICAL SYSTEM | | |
| Maintenance-Free Battery/Charging Capacity/Starter | | |
| 12 Volt/16 amp/solenoid shift | | |
| Ignition | | |
| Breakerless | | |
| Interlock System | | |
| Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are returned to neutral | | |
| ULTIMATE OPERATOR STATION™ | | |
| Operator Platform | | |
| Wide anti-slip platform with dampers; extra-thick pad with logo | | |
| Suspension | | |
| Coil spring suspension with dampening | | |
| Console-Mounted Instruments (Command Center) | | |
| Low engine oil pressure, hour meter, phone/accessory tray with USB charging ports, parking brake indicator light, ignition switch, choke & push/pull PTO switch | | |
| Work Lights | | |
| LED | ● | ● |

| MODEL – CUTTING WIDTH | STAND-ON 52 | STAND-ON 61 |
|---|----------------|----------------|
| TRANSMISSION & STEERING | | |
| Type | | |
| T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, and design-matched Parker high-torque wheel motors | | |
| Filtration/Hydro Fluid | | |
| Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals | | |
| Speed | | |
| 0 – 9.5 mph (0 – 15.3 kph) forward | | |
| 0 – 5.0 mph (0 – 8.0 kph) reverse | | |
| Turning Radius | | |
| True zero degree, turns within own length with counter-rotating, independently powered drive wheels | | |
| Steering | | |
| One- or two-handed operation with dual levers that automatically return to neutral from either forward or reverse position | | |
| Brakes | | |
| Dynamic braking through hydrostatic transmission | | |
| Parking Brake | | |
| Manual lever through linkage to bar in tire (compression) brake | | |
| TIRE SIZES | | |
| Drive Wheels – Standard (5-bolt pattern) | | |
| 23 x 10.5-12, 350 Mag OTR, 4-ply rated | | |
| Front Casters | | |
| 13 x 6.5-6; rib tread, pneumatic with double-sealed bearings to protect from grass wrap | | |
| 13 x 6.5-6; Airless Tweel Caster Wheel | ○ | ○ |
| DIMENSIONS (Mower & Deck) | | |
| Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.) | | |
| 53.0 in. (134.6 cm)/73.0 in. (185.4 cm) | ● | |
| 62.0 in. (157.5 cm)/75.3 in. (191.3 cm) | | ● |
| Height (Command Center – Tower Up) | | |
| 50.0 in. (127.0 cm) | | |
| Height (Command Center – Tower Down) | | |
| 45.5 in. (115.6 cm) | | |
| Drive Tire Track Width (outside edge to outside edge) | | |
| 50.5 in. (128.3 cm) | | |
| WEIGHT | | |
| Uncrated*: (Mower & Deck) 1080 lbs. (489.9 kg) | ● | |
| Uncrated*: (Mower & Deck) 1120 lbs. (508.0 kg) | | ● |
| *DuraMax® deck mulching package kit weights with high-low mulching blades: 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs (16.3 kg). | | |

● Standard ○ Option